⊗BIOESQUE[™]

MOLD RESISTANT COATING





Contains an EPA Registered Fungicide

Resists Mold Growth on Dry Coated Surfaces

Provides Long Term Protection

Durable, Flexible, and Permeable

100% Acrylic Water-Based Coating

Clean White Finish

PROFESSIONAL GRADE

Net Contents: 5 Gallons (18.9 L) KEEP OUT OF REACH OF CHILDREN **SURFACE PREPARATION:** Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue, calcimine, wax, soap and other surface contamination. Clean mold stained surfaces with Bioesque Botanical Disinfectant Solution or Bioesque Rotanical Surface Cleaner and Sealant

Patch irregularities with vinyl patching paste or an appropriate patching compound. Bioesque Mold Resistant Coating is self-priming over bare sheetrock, composition board, ceiling tile and concrete. Recommended for use on wood, plaster, wallboard, sheetrock, concrete, masonry block, primed metal and galvanized metal. Bioesque Mold Resistant Coating may also be used on new structural materials during building construction.

DIRECTIONS FOR USE: Apply Bioesque Mold Resistant Coating generously and uniformly by

brush, roller or airless spray equipment. **Brush:** Synthetic, nylon or polyester bristles **Roller:** Synthetic Fiber 3/8" nap or longer **Spray:** .015 to .019 tip @ 2000-2800 P.S.I.

PRODUCT APPLICATION: Bioesque Mold Resistant Coating is supplied ready to use. Apply one coat of Bioesque Mold Resistant Coating and ensure that the finished surface is properly sealed. To ensure that the finished surface is properly sealed, two-coats may be required on some porous surfaces. Coating will dry White.

COVERAGES:

Smooth Surfaces: 350-600 ft2/gal. Porous Surfaces: 250-300 ft2/gal.

DRYING TIME: @ 70°F 50% R.H To Touch: 1 Hour Recoat: 4-8 Hours

CLEANUP: Clean tools and drippings with warm soapy water before Bioesque Mold Resistant Coating dries. Dispose of waste according to all existing local, state and federal regulations.

STORAGE: Store in a cool, dry environment. Keep container closed when not in use. Do not mix with strong acids or oxidizers. Keep container closed when not in use. Do not freeze. Keep out of reach of children. Follow label instructions. Dispose in accordance with state and local regulations.

In Case of Fire: Use carbon dioxide, dry chemical or foam.

First Aid: If in eyes: Flush immediately with clear running water for 15 minutes. Get medical attention.

If swallowed: Drink large quantities of water and seek medical attention.

If inhaled: Remove to fresh air. If breathing doesn't return to normal, seek medical advice.

If on skin: Rinse with clear water.



Bioesque Solutions 150 East Palmetto Park Rd Suite 110 Boca Baton, FL 33432

www.bioesquesolutions.com

